



### **“Cost Cutter” Cage Features**

- Sturdy base made from two 3” x 8” x 11 gauge. structural tubing and four crossmembers. End crossmembers are “Z” shaped to add impact strength and the two middle crossmembers are made from 2-1/2” x 2-1/2” x 3/16” angle. (Figures 1 & 2)
  - The tubing include formed inserts at high stress points for durability.
- Cage hook anchor point integrated to the base. (Figures 1 & 2)
- “No hang bird” brackets along with the door rod location prevent bird damage while unloading at the processing plant. (Figure 3)
- One piece bumper plates are Bright’s exclusive design to protect the birds against forklift forks damage. (Figures 1 & 2)
- 20 Ga (0.036) thick solid steel top cover from tubing to tubing and act as a shear plate.
- Front uprights are made from 1-1/2” x 2” x 11 gauge. structural tubing.
- The “Double Hollow” high strength aluminum (6063-T6) doors are fitted with galvanized angles. The angles are riveted in place with “Huck” high strength rivets. (Figure 3)
- All Bright’s door hardware is stainless or galvanized steel for durability.
- Standard floors are acrylic chopped fiberglass. (White)
- Two piece back partition in lieu of one partition per floor. This design give more strength to the cage.
- This cage is 35 pounds lighter than the Pro-Plus Premium Cage. That means you can haul 770 more pounds per load.

### **Option Features Available**

- Heavy Duty Base
  - 3” x 8” x 3/16” structural tubing.
  - Three clean out slots per fork tube to reduce weight and prevent litter accumulation.
- Recessed top.
- Uprights made from 2” x 1” x 1/8” channel in lieu of structural tubing.
- Premium green hand-laid fiberglass floors. (The most durable floor on the market)

### **Accessories Available**

- 3,000 lbs. certified cage hook with dual spring.
- 3,150 lbs. certified chain binder.
- Nylon straps.



## Cage Parts

### REPLACEMENT DOOR ASSEMBLY:



- 090-00028NP 3 Door Assembly - Includes an aluminum door with one huck riveted galvanized door angle.
- 090-00028 3 Door Assembly with Pins- Same as above with the addition of a long and short shouldered hinge pin.
- 090-00030 3 Door Assembly with Hardware-Same as above including hinge pins, with the addition of a galvanized door rod, a stainless steel spring, stainless steel spacer clip, one stainless steel 1/4" washer, and one stainless steel 3/16" washer.
- 090-00025NP 2 Door Assembly - Includes an aluminum door with two huck riveted galvanized door angle.
- 090-00025 2 Door Assembly with Pins-Same as above with the addition of a long and short shouldered hinge pin.
- 090-00027 2 Door Assembly with Hardware-Same as above including hinge pins, with the addition of two galvanized door rods, two stainless steel springs, a stainless steel spacer clip, two stainless steel 3/16" washers, and two stainless steel 1/4" washers.
- 090-00226NP Roaster Door Assembly - Includes an aluminum door with two huck riveted galvanized door angles.
- 090-00226 Roaster Door Assembly with Pins- Same as above with the addition of a long and short shouldered hinge pin.
- 090-00227 Roaster Door Assembly with Hardware-Same as above including hinge pins, with the addition of two galvanized door rods, two stainless steel springs, stainless steel spacer clip, two stainless steel 3/16" washers, and two stainless steel 1/4" washers.

\*ALL DOOR ASSEMBLIES ARE HOLLOW HINGED, TOP AND BOTTOM, WITH 3" GALVANIZED ANGLE BRACKET ATTACHED. ( 1 HINGE FOR 3 DOOR, 2 HINGES FOR 2 DOOR AND ROASTER)