

Description

Stackable coops are 65" wide, 102" in length, and 20" high. Coops floor and top material are hand-laid woven fiberglass matting with reinforced edges. Door opening is 18" in height and 56" in width for easy loading and unloading. Coops can be "Hot Dipped" in "Prime Western Zinc" for a corrosion resistant galvanized finish. A standard load of coops is designed to fit on a 48' trailer and contains eight stacks of five coops for a total standard load of forty coops.

"Bright" manufactured "Stackable" turkey coops have been designed to provide maximum coop life for years of trouble free service in the field.

Removable / Stackable" Live Turkey Transport Coops

Structure

Tube uprights are 2" x 1" tubing while the horizontal members are 1" x 1" tubing. All tubing wall thicknesses are .120 (11 gauge) for strength and durability. Our partitions are heavy duty gauge wire with four larger horizontal rods for added strength.

Doors

Standard coops have "Easy Clean" overhead doors on each end with two positive aluminum latches per door. The doorway opening is 18" x 56" for easy loading and unloading.

Floor and Top

Coops floor and top are green hand-laid woven fiberglass with reinforced edges. Floor and top secured by wide angle hold downs, as well as stainless steel rivets on the top and in the doorway opening.

Finish


The galvanized finish is highly recommended by Bright Coop, Inc. to protect against corrosion. This finish supports a five year warranty against rust out. Galvanized coops have been dipped in "Prime Western Zinc" inside and out for extended life. There is also a non-galvanized option.


Dimensions

Each coop is 20" overall height, 65" overall width (including lifting lugs), and 102" overall length. Our galvanized coop weighs approximately 364 pounds, while the approximate weight of the non-galvanized option is 340 pounds.

Securement

Coops are stacked five high with eight stacks on a 48' trailer or nine stacks on a 53' trailer and are secured with Bright's cage hooks and 4" nylon straps with "D" ring.





Manufactured under U.S. Patents #6,694,918 and #7,261,059